AEROTRAIN - DULLES AIRPORT TRAIN SYSTEM

hen Washington Dulles International Airport's automated airport train system – AeroTrain – goes into service, airline passengers will have a convenient and comfortable train system to transport them between the Main Terminal and Midfield Concourses. It will handle more riders and move more efficiently than the current Mobile Lounges.

The Metropolitan Washington Airports Authority contracted with Sumitomo Corporation of America who, working with Mitsubishi Heavy Industries, designed, engineered, constructed, and delivered the rubber tire trains to Dulles. When AeroTrain begins service, they will also operate and maintain the system for five years.

The AeroTrain system is similar to other Mitsubishi systems currently operating in Hong Kong, Singapore, Tokyo, Yokohama, Hiroshima, Kobe, and other locations.

Phase One

The AeroTrain system will replace most of the Mobile Lounges currently transporting passengers between the Terminal and Midfield Concourses.

NET ROZOUTAN WASHINGTON
ASPORTS AUTHORITY


The first phase of the project includes a train station at the Main Terminal and tunnels that will connect the Terminal to the east and west ends of Concourse B. This phase also includes construction of a train station at the site of a future

permanent Midfield Concourse that will be built when future demand requires. In the interim, passengers will enter Concourses C/D through a connecting passenger tunnel equipped with moving walkways.

The Main Terminal Train Station will be reached through two new spacious, subsurface security screening areas. Once beyond security, passengers may continue to the Z-Gates located at the Terminal, use the passenger walkway to Concourses A and B, or board AeroTrain to the Midfield Concourses. The stations in the Concourses are located at convenient points to minimize walking distances to airline gates.


The Final Layout

The Master Plan for Washington Dulles International Airport envisions a future that consists of the existing Main Terminal (located at the north end of the airport) and a new "South" Terminal, with four permanent midfield concourses in between. The AeroTrain system will develop concurrently with each new facility until it finally joins into one continuous "loop."



AEROTRAIN - DULLES AIRPORT TRAIN SYSTEM





PROJECT SCHEDULE	
Construction Start -Tunnel	October 2002
Notice to Proceed - System	March 2003
First Vehicle Delivery	April 2007
	4 Vehicles
V	EHICLE DATA
Model of Vehicle	Crystal Mover
Vehicle Fleet	29
Brakes	Electric Command
Train Consist	3-Car Trains (Initial)
	4-Car Trains (Maximum)
Maintenance & Recovery Vehicle	1
Vehicle Size	8'9" wide x 40'5/16" long
Door Openings	78" high and 72" wide
Vehicle Weight (empty)	38,493 pounds
Vehicle Build	Mihara Japan
Number of Seats	8
Number of Passengers	72
Tires	Inflatable Rubber with inner safety wheel
Vehicle Material	Aluminum Alloy, Welded
MAJOR SUBSYSTEMS	
Signaling	Radio Based, Fixed Block
Power Supply	750 Vdc rail power
Power Consumption	11,547 Mega Watts per year
Power Collection	Guideway -Mounted Power Rail
Traction Power Substation	3
Communications	Public Address System, Train Radio,
	CCTV, Dynamic Signs, Phone System
Head Way	2 minutes (Peak)
	4 minutes (Off Peak)
Guidance	Side Guide Beam

SYSTEM DESCRIPTION	
System Prov ider	Mitsubishi Heavy Industries
Maintenance Building Location	Off – Service Line
Number of tracks	2
System Operation	1 Pinched Loop (Operation), Dual Loop (final)
Train Control	Fully Automated
Peak Hour Capacity (PPHPD)	6,755 passengers per hour per direction (Operation) 9,007 passengers (final)
Maximum Grade	2.6%
Top Speed	43.5 miles per hour (Auto Operation)
	5 miles per hour (Manual Operation)
Round Trip Time	806 seconds
Airside System	100%
Underground Guideway Length	3.78 miles
System Life	25 Years
FIXED FACILITIES	
Switches	30
Number of Stations	Dual Side-Center Platform
	4 (Phase 1), 10 (Final)
Number of Station Doors	32
Average Station Spacing	1970 feet
Platform Length	400 ft. Main Terminal
-	170 ft. other stations
Station Features	Elevator & Escalator
Maintenance Building Size	67,553 square feet
Yard Operation	Automated
Maintenance Building Storage	24 Vehicles
Maintenance Yard Storage	20 Vehicles
Car Wash	1 Automated
C	ONTRACT TERM

MAIN TERMINAL TRAIN STATION

he Main Terminal AeroTrain Station construction site was excavated to approximately 60 feet below ground, directly adjacent to the Main Terminal on the airfield side of the Terminal, and spans its entire length (approximately 1,600 feet) from west to east.

It has four distinct levels: Departures (49,600 square feet), Arrivals (49,600 square feet), Security Mezzanine (121,700 square feet), and the Train Platform (54,500 square feet).

The Security Mezzanine provides critical floor space for a new, expanded passenger security screening function that will provide for more efficient passenger screening and alleviate congestion on the Main Terminal Ticketing Level. Passengers with boarding passes, who do not need to check luggage, will be able to proceed directly to the Security Mezzanine.





The Train Platform has a side-center-side arrangement that will allow departing passengers to enter the train from the center platform after arriving passengers, bound for baggage claim, exit the train onto the side platforms and proceed up to the ground floor (Bag Claim Level) of the Terminal.

The Terminal Station is a bright and airy space. Skylights at roof level allow natural light to filter all the way down to the train platforms and will be supplemented by artificial light designed to play off the glass forms and stainless steel surfaces of the station.

MAIN TERMINAL TRAIN STATION FACTS:

Notice to Proceed: October 2002 Forecast Completion: July 2009

Contractors

Design: Skidmore, Owings and Merrill **Turner Construction Company** Construction:

Schedule: 7 years/5 milestones Labor:

Up to 300 people per day (two shifts)

estimated 3.8 million manhours at completion

Number of Subcontractors:

Four Levels:

Departures (Ticketing) Level: 49.600 sf Arrivals (Baggage Claim) Level: 49.600 sf Security Mezzanine Level: 121,700 sf AeroTrain Platform: 54.500 sf Total Building Square Footage: 275,400 sf

Total TSA Security Checkpoints: 26-34 (depending on final TSA configuration)

Elevators: 20 **Escalators:** 36 Stairwells: 23 public **MUFIDS:** 16 20 Mobile Lounge Docks:


MAIN TERMINAL TRAIN STATION


Train Platform - 40 feet below ground,

54,500 square feet

Departing Passengers:

- From ticketing and bag claim levels, descend to security mezzanine
- 2Go through TSA Screening
- **8** Descend to train platform
- Board AeroTrain





Arriving Passengers:

- Arrive on AeroTrain
- Ascend to platform bridge
- **S**Ascend to baggage claim area

MAIN TERMINAL TRAIN STATION FACTS (continued)

 Excavation:
 220,000 cy

 Backfill:
 24,000 cy

 Rebar:
 5,300 tons

 Concrete:
 47,000 cy

 Terrazzo Floor:
 186,000 sf

Pre-Cast Wall Panels: 600 each/36,000 sf

Skylights: 140

Train Tube Glass pieces: 765 each/25,200 sf

Curtainwall/Clerestory: 11,000 sf
Plinths: 4,800 lf
Power Rails: 2,400 lf
Guiderails: 5,000 lf
Switches: 4

Air Conditioning Load: 1,425 tons
Heating Load: 7,760 MBTU's

Substation Size: 2 substations @ 3,300 kw each

Kingpost Truss Span: 105 ft

Cable Size: 2 ½ in diameter (minimum breaking strength of 432 tons each)

Cable Load: 250 kps

Micropiles: 164 permanent (plus 30 temporary)

Support of Excavation: 123,000 sf

TIER 1/CONCOURSE B WEST TRAIN STATION

The Tier 1 East and West Train Stations will serve Concourses A and B.

The Tier 1 West Station was constructed under the same contract as the 15-Gate Addition to Concourse B, that opened in January 2008. Passengers arriving at the Concourse B West Station will exit onto side platforms, while other passengers depart the Station via the center platform.

The materials in the station are the same neutral color palette as Concourse B, but with more texture, translucency and depth. Major finishes include terrazzo flooring, exposed aggregate concrete columns, porcelain enamel and ceramic tile for walls and fascia, stainless steel panels, aluminum for wall and base details, and transparent and translucent glass for the train enclosure walls to allow passengers to view trains as they pass through the station.

TIER ONE WEST/CONCOURSE B TRAIN STATION FACTS:

Notice to Proceed: September 2005 Forecast Completion: October 2008

Contractors

Design: Hellmuth, Obata + Kassabaum
Construction: Balfour Beatty Construction

Schedule: 3 years/9 milestones

Total Manhours: 1,250,066

Number of 1st Tier Subcontractors: 60 Total Subcontractors and Suppliers: 260

Five Levels:

 Club:
 14,060 sf

 Concourse:
 32,385 sf

 Apron:
 25,489 sf

 Mezzanine:
 35,375 sf

 Platform:
 42,290 sf

 Total Building Square Footage:
 152,599 sf

Space Allocations:

 Concessions:
 15,000 sf

 Concessions Support:
 2,000 sf

 Tenant:
 2,200 sf

 Elevators:
 12

 Escalators:
 10

 Stairwells:
 18

MUFIDS: 2 banks - 12 monitors/ bank located in existing Concourse

Excavation: Excavated under previous contract

 Structural Steel:
 1,000 tons

 Rebar:
 180 tons

 Concrete:
 19,800 cy

 Terrazzo Floor
 36,500 sf

 Curtainwall/Clerestory:
 7,500 sf

 Plinths:
 2,050 lf

 Power Rails:
 1,025 lf


Switches: 2

Electrical Service: Substation #7 with dual 15kv feeders, 750 kW Emergency


TIER 1/CONCOURSE B WEST TRAIN STATION

MEZZANINE LEVEL





PLATFORM LEVEL







Non-Passenger Areas Maintenance Corridors

Passenger Areas

Open-To-Below

APRON LEVEL

TIER 1/CONCOURSE A/B EAST TRAIN STATION

The East Station is located beneath the east end of Concourse B. Initially, due to site constraints, the Concourse A/B East Station will operate in a center platform configuration. Passengers will arrive at and leave the Station from a single platform. It will eventually be expanded into a side/center/side configuration.

The East Station atrium center has been designed as a destination space emphasized by high ceilings, clerestories, and natural light. Finishes have been selected to coordinate and expand upon the finishes in the existing Concourse B. The color palette retains the existing whites, grays, and silvers, while adding new materials, including exposed aggregate concrete columns, porcelain enamel panels on the walls, terrazzo flooring, and a transparent glass train enclosure to allow passengers to view trains from the center platform as they pass through the station.

TIER 1 EAST/CONCOURSE A/B TRAIN STATION FACTS:

Notice to Proceed: October 2004 Forecast Completion: June 2009

Contractors

Design: Hellmuth, Obata + Kassabaum Construction: Clark Construction Group Schedule: 3.5 years/25 milestones

Total Manhours: 2,462,561

Number Subcontractors and Suppliers: 70

Four Levels:

 Concourse:
 7,218 sf

 Apron:
 11,485 sf

 Mezzanine:
 57,223 sf

 Platform:
 42,582 sf

 Total Building Square Footage:
 118,508 sf

Elevators: 4
Escalators: 8
Stairwells: 8

MUFIDS: 1 bank - 12 monitors/bank located in existing Concourse

 Excavation:
 103,000 cy

 Structural Steel:
 5,400 cy

 Rebar:
 2,550,000 lbs

 Concrete:
 17,000 cy

 Terrazzo Floor:
 25,000 sf

 Plinths:
 1,700 lf


 Power Rails:
 850 lf

 Switches:
 2

Air Conditioning Load: 620 tons
Heating Load: 5,000 MBTUH
Substation Size: 2500KVA

Support of Excavation: Bolts, Shotcrete and wire mesh, 50,400 sf


TIER 1/CONCOURSE A/B EAST TRAIN STATION







PLATFORM LEVEL







Passenger Areas Non-Passenger Areas Maintenance Corridors

APRON LEVEL

TIER 2/CONCOURSE C EAST TRAIN STATION

he Concourse C East Station is being built under the location for a future permanent midfield concourse.

The platform has a side/center/side configuration. In the near term, the Concourse C East Station will serve existing Concourse C passengers via a temporary pedestrian connector tunnel equipped with moving walkways. In the long term, this Station will serve the eastern half of a future 44-gate, domestic and international Midfield Concourse.

The interior finishes for the station include metallic tile walls, inclined stainless steel panel ceilings, with wood and stainless steel accents. Both direct and indirect lighting will illuminate the facility.

TIER 2 EAST/CONCOURSE C TRAIN STATION FACTS:

Notice to Proceed: March 2005 Forecast Completion: May 2008

Contractors

Design: Kone Pederson Fox Associates
Construction: Facchina Construction Company

Schedule: 39 months/13 milestones

Substantial completion on schedule

Total Manhours: Up to 180 people per day

Total On-Site Subcontractors: 25 total

Five Levels:

Tier 2 Concourse Apron Level: Tier 2 Concourse Basement Level:

Station Mezzanine Level: Sation Platform Level: Track/Pump Room Level

Total Building Square Footage: 234,215 sf Elevators: 2 plus 4 future

Escalators:

Stairwells: 2 dual exit stairwells configured to serve all 3 platforms and mezzanine

MUFIDS: None in station, provided inside Concourse C portal

Excavation: 254,000 cy Backfill: 65,000 cy Rebar: 4,200 tons Concrete: 34,470 cy Concrete Formwork: 770,000 cy Terrazzo Floor: 20,000 sf Curtainwall/Clerestory: 740 sf Plinths: 1,925 lf


Power Rails 1,000 lf approx. Guiderails: 1,900 lf approx.

Switches:


Heating Load: 2,700 MBTU's
Air Conditioning Load: 400 tons
Substation Size: Dual 2,500 KVA
Support of Excavation: 13,000 sy

Asphalt Pavement: 38,150 sy (including Bypass Taxilanes)
Concrete Pavement: 30,305 sy (including Bypass Taxilanes)

TIER 2/CONCOURSE C EAST TRAIN STATION




PLATFORM LEVEL






Passenger Areas Non-Passenger Areas Holding Area

TIER 2/CONCOURSE C CONNECTOR TUNNEL





TIER 2 EAST/CONCOURSE C CONNECTOR TUNNEL FACTS:

Notice to Proceed: November 5, 2007

Forecast Completion: May 2009

Contractors

Design: Kone Pederson Fox Associates
Construction: Clark Construction Group

Schedule: 19 months/multiple phases and milestones

Substantial completion on schedule

Three Levels:

Tunnel Level (approx. Station Mezzanine Level)

Apron Level at Concourse C Concourse Level at Concourse C

Total Connector Building and Tunnel: 25,740 sf

Tunnel Inside Dimensions: 30 ft wide x 450 ft long

Elevators: 2 Escalators: 4

Stairwells: 3 - 2 New in Connector Building, 1 existing in Station

MUFIDS: Provided just inside Concourse C portal


Mobile Lounge Docks: None. Existing C docks will be closed when APM begins service.

Moving Walkways: 2/250 ft long Walk from Center Platform to Concourse C: 3-5 minutes


Excavation: 30,000 cy Rebar: 630 tons Concrete Formwork: 100,000 cy Cast-in-Place Concrete: 6,800 cy Concrete Pavement Replacement: 5,000 sy Structural Steel: 52 tons Air Conditioning Load: 610 tons 1,300 mbh Heating Load:

Substation Size: Powered from Concourse C and Tier 2 Station


TIER 2/CONCOURSE C CONNECTOR TUNNEL




MEZZANINE LEVEL W/CONNECTOR



MEZZANINE LEVEL



PLATFORM LEVEL




VEHICLE MAINTENANCE FACILITY

The AeroTrain Vehicle Maintenance Facility (VMF) is a multi-use facility from which all of the testing, operation, and monitoring of the AeroTrain System, as well as all of the heavy and light maintenance of the AeroTrain cars, will take place.

Major components of the VMF comprise a Vehicle Wash Facility, Switchyard, Light and Heavy Maintenance Bays, the Central Control Facility and Equipment Room, and a Shop and Storage Area.







TUNNELS

he total AeroTrain system tunnel length is approximately 19,958 track feet (3.78 miles). Three tunneling methods were used to excavate these tunnels.

The first method, called "cut and cover," was used to excavate approximately 7,700 track feet with a process that involves excavating a large trench down from the surface. This method was used close to existing facilities and where above ground access was available without disrupting airport activity.

The New Austrian Tunneling Method (NATM), a more traditional system of mining, was used in areas where the tunnels curve (3,650 track feet). NATM uses a combination of means to grind the rock face in layers. Shotcrete is



Cut and Cover

immediately applied to the exposed tunnel walls to provide support.

Finally, the Tunnel Boring Method (TBM) was used to bore approximately 4,300 track feet, for the straight tunnel runs. The 23' diameter machine, known as a mole, bored through solid rock, approximately 55' below grade. Precast concrete wall lining segments were mechanically put into place by the mole as it moved forward.





AEROTRAIN SUMMARY FACTS

General Information:

Number of Cars: 29

Waiting Time: 1.9 minutes
 Maximum Speed: 42 mph
 Distance Between Stations: 2,150 feet
 Travel Time Between Stations: 72 seconds

Dimensions:

Phase 1

Total Track Feet: 19,958 (3.78 miles)

Main Terminal 440 feet long x 120 feet wide x 39 feet high

Station: (public area)

Concourse 180 feet long x 120 feet wide x 30 feet high

Stations: (typical public area)

Tunnels: 16 feet x 18 feet

Contractors:

Train and Systems:

Design/Build: Sumitomo Corporation of America

Main Terminal Train Station:

Design: Skidmore, Owings and Merrill Construction: Turner Construction Company

Concourse A-B Train Stations:

Design: Hellmuth, Obata & Kassabaum Construction: Atkinston/Clark/Shea (East Station)

Concourse C Train Station:

Design: Kohn Pederson Fox Associates, P.C. Construction: Facchina Construction Company, Inc.

Tunnels and Vehicle Maintenance Facility

Design: HNTB Corporation

Construction: Turner Construction Company (VMF)

Atkinson/Clark/Shea (East Tunnels)

Clark/Shea (West Tunnels)

Estimated Completion:

Main Terminal Station and Train to Concourses A, B and C: 2009

Estimated Program Costs:

Trains and System: \$215 million

Tunnels, Station Shells

& Maintenance Facility: \$519 million

Main Terminal Train Station

and Security Mezzanine: \$395 million

Concourse Stations (3):

Tier 1/A-B East, Tier1/B West, Tier 2/C \$285 million